



ACCESS 10



Fingerprint Access Control System

Storage Capacity

Finger Capacity	500
Card Capacity	500(non-standard)
Code Count(password)	2
Verification time	<=1.5 Second
Relay	Yes
FAR	0.00001%
FRR	0.001%
Door Controlled	1
Linking mode	Offline
Power Source	12DC/1.5Amp
LCD display	Black-White Screen
Verication Mode	Fingerprint, Card, Password
Operating temperature	0°c ~ 45°c
Dimensions	86*86*26 mm



Access 10

Biometric

Sensor type	500 DPI
FAR	0.00001%
FRR	0.001%
OS	RTOS
Verification time	<=1 second
RF card options	125kHz EM (Standard)

Audio/Visual

LCD	black-white screen
Voice instruction	16-bit Hi-Fi voice & sound indication
Language	English

Access control

Relay	YES
Support	Remote, Push Button, No Touch

Power & Enviroment

Inbuilt Battery Backup	YES
Operating Temperature	0°C ~ 50°C
Power	12V DC / 2A
Dimension (L*H*W)	86 x 86 x 26 mm



Accepts moist and rough Finger



Access Control



Compact & lightweight design



Unaffected by High
Temperatures 0° ~ 50°

Disclaimer : Brief specifications are mentioned here. specification may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development.

Certified by



www.biomaxsecurity.com

Connect with us on



BiomaxOfficial



BioMax Security



biomaxsecurity



BioMax Access Control