Powered By eSSL



Multi-Biometric Time Attendance & Access Control System

MB160





Specification

Storage Capacity

Face Capacity : 1,500 Fingerprint Capacity : 2,000 ID card Capacity : 2,000 Transaction Capacity : 1,00,000

Visual Display : 2.8-inch TFT Screen

Communication Communication : TCP/IP, USB-Host Push Data : Yes

Standard Functions SMS, DLST, Scheduled-bell, Self-Service Query, Automatic Status Switch, T9 Input, Photo ID, Camera, Multi-verifcation

Interface for Access Control

3rd Party Electric Lock, Door Sensor, Exit Button, Alarm

Optional Function

ID , Work Code, RS232 Printer

Power & Environment

Battery : (Optional) Power Supply : DC 12V --- 1.5A Verifcation Speed : ≤0.5 Sec Operating Temperature : 0°C - 45°C Dimension (in mm) : (L)167.5 x (W)148.8 x (H)32.2

Features

- High verification speedProfessional firmware and platform make it more flexible
- Intuitive and stunning UI design
- Sophisticated and lightweight design, fits in any environment

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development www.esslsecurity.com

FCCC RoHS