Powered By eSSL



Multi-Biometric Time Attendance & Access Control System

MB20





Specification

Storage Capacity

Face Capacity : 500 Fingerprint Capacity : 2000 User Capacity : 1000 Transaction Capacity : 50,000

Visual & Audio Display : 2.8" Color LCD Sound : Stereo Speaker

Communication Communication : TCP/IP, USB-Host Push Data : Yes

Standard Functions Automatic Status Switch, Self-Service Query, DST, T9 Input, 9Digit User ID,Scheduled Bell, Photo ID, Lock, Sensor, Exit Button

Power & Environment

Power Supply : DC 5V --- 0.8A Operating Temperature : 0°C - 45°C Operating Humidity : 20% - 80% Dimension (in mm) : (L)161.93 x (W)152.82 x (H)30.59

Features

-- Fingerprint, face, RFID and password

4 type verification mode

- -- High-speed identification less than 1 second
- -- TCP/IP Port for Internet connection
- -- Access Port available to control one lock and exit button
- -- Optional 5V 1900mAH UPS, standby up to 3 hours

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development www.esslsecurity.com