Powered By eSSL



Multi-Biometric Time Attendance & Access Control System

SFace900



Face Capacity: 3,000 Fingerprint Capacity: 4,000 Card Capacity: 10,000 Logs Capacity : 100,000 **Display : 4.3-Inch Touch Screen** Communication : TCP/IP, USB Host, **Standard Functions : Automatic** Status Switch, Self-Service Query, Work Code, SMS DST, T9 Input, 9 Digit User ID, Scheduled Bell, Photo ID Interface for : 3rd Party Electric Lock, Door Sensor, Exit Button, Alarm **Wiegand Signal Output Optional Functions : ID/MiFareCard, Wi-Fi,** 3G, ADMS, 2000 mAH Backup Battery Power Supply: 12V 3A Operating Temperature : 0 °C- 45 °C **Operating Humidity : 20%-80%** Dimensions :195.5*166.5*120mm (Length*Width*Thickness) Package Weight : 1.6 kg



Features

- 3,000 face and 4,000 f
- Multi-languages
- High verification Speed
- Optional battery backup
- One face template is registered for one user only
- Able to detect whether the face is an actual face or a photo, enhancing the security level of verification
- Outside installation (maximun 12,000 lux)

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development www.esslsecurity.com