Powered By eSSL



Multi-Biometric Time Attendance &

Access Control System

SilkBio-101TC

Specification

Storage Capacity

Face Capacity : 2,000 Fingerprint Capacity : 3,000 ID Card Capacity : 3,000 Transaction Capacity : 1,00,000

Communication TCP/IP, USB-Host, Wi-Fi(Optional) Push Data : Yes

Standard Functions

Work Code, SMS, DST, Scheduled-bell, Self-Service Query, Automatic Status Switch Photo ID, T9 Input, Camera, 9 digit user ID, Built-in Battery, Multiple Verify Mode, External Bell Access Control Interface : Lock, Door Sensor, Exit Button, Alarm

Optional Optional Functions : Mifare

Visual Display : 2.8-inch TFT Screen

Power & Environment

Operating Temperature : 0°C ~ 45°C Power Supply : DC 12V --- 1.5A Operating Humidity : 20% - 80% Dimensions (in mm) : (L)180 x (W)154 x (H)34.2

Features

- Multi-biometric fast verification
- Touch Keypad
- Infrared auto-turning on function to save power
- Quick recognition of dry, wet and rough fingers
- Multi-language supported
- Built-in 2000mAh backup battery to extend operation time
- Prevents duplicated face registration and supports fake face detection function

Disclaimer: Brief specifications are mentioned here.Specifications may change without prior notice. Customers are advised to check with us before purchase. Actual product may differ slightly to that depicted for ongoing product development www.esslsecurity.com



