

Fingerprint Time and Attendance System



Specification

UA300

Fingerprint Capacity: 3000 templates

Card Capacity: 10,000 (optional)

Transaction Capacity: 1,00,000 logs

CPU: 800 MHz processor

Display: 3" TFT screen

Verification Speed: <=0.5 sec

FAR: <= 0.0001%

FRR: <=1%

Communication: TCP/IP, USB host & client

Optional ID/Mifare card reader

Power Supply: 5V DC, 2A

Operating Temperature: 0°C - 45°C

Operating Humidity: 20% - 80%

Dimension(L x W x T): 180 x 135 x 37 mm

Standard Functions:

- Webserver, Workcode, Scheduled-bell
- > Self-Service Query, SMS, 9 digit user ID
- > Automatic Status Switch, T9 input

Features:

- Intuitive and stunning UI designed with the most popular and internationalized factor.
- Interface operation adopts modularized hierarchical design.
- ➤ Faster matching speed: less than 0.5 sec.
- > Support user validity settings.
- > Support data backup and retrieve.
- Support advanced workcode consisted of letters and numbers.

Disclaimer: Brief specifications are mentioned here. Specifications may change without prior notice. Customers are advised to check with us before purchase.

Actual product may differ slightly to that depicted for ongoing product development

www.esslsecurity.com